

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0260-15	25 ... 6000 MHz	15 / 20	42 / 46 ± 4	12 / 12	260	2 HU, 430 mm	14
BLWA 0260-25D	20 ... 6000 MHz				500	3 HU, 430 mm	20
	20 ... 1000 MHz	25 / 30	44 / 46 ± 2	20 / 20			
	1000 ... 6000 MHz	25 / 30	44 / 46 ± 2	20 / 20			
BLWA 0260-30/10D	20 ... 6000 MHz				320	3 HU, 430 mm	18
	20 ... 1000 MHz	30 / 35	44.8 / 47 ± 2	20 / 20			
	1000 ... 6000 MHz	10 / 13	40 / 43 ± 3	20 / 20			
BLWA 0260-40D	20 ... 6000 MHz				600	3 HU, 430 mm	20
	20 ... 1000 MHz	40 / 45	46 / 48 ± 2	20 / 20			
	1000 ... 6000 MHz	40 / 45	46 / 49 ± 3	15 / 20			
BLWA 0260-50/25D	20 ... 6000 MHz				550	3 HU, 430 mm	20
	20 ... 1000 MHz	50 / 60	47 / 49 ± 2	20 / 20			
	1000 ... 6000 MHz	25 / 30	44 / 47 ± 3	20 / 20			
BLWA 0260-50D	20 ... 6000 MHz				600	3 HU, 430 mm	20
	20 ... 1000 MHz	50 / 55	47 / 49 ± 2	20 / 20			
	1000 ... 6000 MHz	50 / 55	47 / 50 ± 3	18 / 20			
BLWA 0260-100D	20 ... 6000 MHz				1100	4 HU, 630 mm	38
	20 ... 1000 MHz	100 / 120	50 / 52 ± 2	20 / 15			
	1000 ... 6000 MHz	100 / 120	50 / 53 ± 3	15 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm