

STANDARD MODELS

Model	Frequency Range	Output Power P _P min / Duty W _{pk} / %	Pulse Width max. **)	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 1025-1000	1 ... 2.5 GHz	1000 / 10	100 µs	60 / 63 ±3	15 / 15	1500	4 HU, 630 mm	37
BPA 1025-2000	1 ... 2.5 GHz	2000 / 10	100 µs	63 / 66 ±3	15 / 15	3000	7 HU, 630 mm	75
BPA 1025-3000	1 ... 2.5 GHz	3000 / 10	100 µs	64.8 / 68 ±3	15 / 15	4500	10 HU, 630 mm	110
BPA 1025-4000	1 ... 2.5 GHz	4000 / 10	100 µs	66 / 69 ±3	15 / 15	6000	12 HU, 630 mm	150
BPA 1025-6000	1 ... 2.5 GHz	6000 / 10	100 µs	67.8 / 71 ±3	15 / 15	9000	18 HU, 800 mm	200
BPA 1025-7500	1 ... 2.5 GHz	7500 / 10	100 µs	68.8 / 72 ±3	15 / 20	10000	21 HU, 800 mm	330
For individual data sheets, please click on the above model name								1 HU = 44.45 mm